

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

Claims 1-10 (canceled).

Claim 11 (new): A display system, which includes a display device and a device provided on a display section of the display device and having one or more conductive thin plates, said display system comprising:

a display device driving section arranged to drive the display device; and

a signal application section arranged to apply, to the device having the one or more conductive thin plates, a noise canceling signal having an amplitude and a phase that are equal with an amplitude and a phase of a driving signal applied from the display device driving section to the display device.

Claim 12 (new): The display system according to claim 11, wherein the device having the one or more conductive thin plates includes two conductive thin plates overlapping each other, and the noise canceling signal is applied to at least a conductive thin plate of the two conductive thin plates which is located closer to the display section of the display device.

Claim 13 (new): The display system according to claim 11, wherein the device having the one or more conductive thin plates is an input device arranged to detect a position via which information is inputted from outside.

Claim 14 (new): The display system according to claim 13, wherein the input device has two conductive thin films overlapping each other, and the noise canceling signal is applied to at least a conductive thin plate of the two conductive thin plates which is located closer to the display section of the display device.

Claim 15 (new): The display system according to claim 13, wherein the input device includes:

an input device control section to which a detection signal to detect a position via which information is inputted from outside to the conductive thin plate; and

a signal switching section arranged to select either the noise canceling signal or the detection signal so as to input the selected signal to the conductive thin plate.

Claim 16 (new): The display system according to claim 15, wherein the signal switching section switches the noise canceling signal to the detection signal or switches the detection signal to the noise canceling signal in accordance with whether or not information is inputted from outside to the conductive thin plate.

Claim 17 (new): The display system according to claim 15, wherein in a case where the display system is provided on a device having at least one of a telephone function and a sound collecting function, the signal switching section selects the noise canceling signal in using said at least one of the telephone function and the sound collecting function so as to input the noise canceling signal to the conductive thin plate.

Claim 18 (new): The display system according to claim 15, wherein the input device further includes a conversion circuit arranged to convert an amplitude of the noise canceling signal before inputting the noise canceling signal to the input device control section.

Claim 19 (new): The display system according to claim 11, wherein the display section of the display device is a liquid crystal panel which has two substrates and liquid crystal provided between the two substrates, and the noise canceling signal has an amplitude and a phase that are equal to an amplitude and a phase of a driving signal which influences electric charge existing between the liquid crystal panel and the one or more conductive thin plates.

Claim 20 (new): The display system according to claim 11, wherein the display section of the display device is a liquid crystal panel which has two substrates and liquid crystal provided between the two substrates, a thin film transistor is provided on a substrate of the two substrates which is positioned further from the one or more conductive thin plates, and the noise canceling signal has an amplitude and a phase that are equal to an amplitude and a phase of a driving signal applied to a substrate of the two substrates which is positioned closer to the one or more conductive thin plates.